



ZVÁRANÉ SIETE

z rebrovaného drôtu

BSSt 500 M, (DIN 488)

BSSt 550 M, (ÖNORM B 4200-7)

Označenie	≥ drôtu	šírka x dĺžka	rozmer oka	Teoretická hmotnosť
	(mm)			(kg/ks)
KA 16	4/4	2000x3000	100/100	11,880
KA 17	4/4	2000x3000	150/150	8,120
KA 18	4/4	2000x3000	200/200	5,940
Q 84	4/4	2150x5000	150/150	14,450
AQ 42	4,2/4,2	2400x6000	100/100	31,390
KD 35	5/5	2000x3000	100/100	18,500
KD 37	5/5	2000x3000	150/150	12,640
KD 36	5/5	2000x3000	200/200	9,250
Q131	5/5	2150x5000	150/150	22,500
AQ 50	5/5	2400x6000	100/100	44,380
AQ 60	6/6	2400x6000	100/100	63,940
AQ 70	7/7	2400x6000	100/100	86,980
KH 20	6/6	2000x3000	150/150	18,200

Označenie	≥ drôtu	rozmer oka	šírka x dĺžka	Teoretická hmotnosť
	(mm)			(kg/ks)
KH 30	6/6	2000x3000	100/100	26,640
KH 31	6/6	2000x3000	200/200	13,320
Q 188	6/6	2150x5000	150/150	32,400
KY 14/86	8/8	2400x6000	150/150	75,840
KY 18/49	8/8	2000x3000	100/100	47,400
KY 50	8/8	2000x3000	150/150	32,400
KY 51/57	8/8	2000x3000	200/200	23,700
KY 81	8/8	2150x5000	100/100	85,910
Q335A	8/8	2150x5000	150/150	57,700
KY 85 AQ80 KY95	8/8	2400x6000	100/100	113,800

* Možnosť dodania sietí aj na základe výkresovej dokumentácie.